

# PROJECTOR 100

## PROJECTOR 100

### BUILDINGS & CONSTRUCTION

#### Applications

For spraying of wet mortar, mixed concrete and other wet products.  
Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

#### Advantages

- High working pressure.
- Light weight, flexible and easy to handle.
- Abrasion resistant tube.

#### Technical description

**Inner tube:** wear resistant NR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** wear and weather resistant SBR, black, fabric impression.

**Temperature range:** -30 °C to +70 °C.

**Electrical properties:** conductive tube,  $R < 2 \cdot 10^6 \Omega/m$ .

#### Special properties:

abrasion resistance of tube <70mm<sup>3</sup> according to ISO 4649.

#### Complementary information

13.3m lengths available on request, min. order is three pieces and by multiple of three.

Other wall thickness and/or bursting pressure on request.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
25	7.0 +0/-1	39 ±1.0	40.0	100	100	0.87	40	0061494	•
32	8.0 +0/-1	48 ±1.0	40.0	100	150	1.24	40	0127153	400
35	6.5 +0/-1	48 ±1.0	40.0	100	180	1.06	40	0061496	•
38	10.0 +0/-1	58 ±1.0	40.0	100	180	1.84	40	0127156	200
40	10.0 +0/-1	60 ±1.0	40.0	100	200	1.92	40	0127170	200
50	7.5 ±0.7	65 ±1.5	40.0	100	370	1.64	40	0127179	400
	9.0 ±0.7	68 ±1.5			280				
60	10.0 ±0.7	80 ±1.5	40.0	100	340	2.72	40	0127183	160
65	10.0 ±0.7	85 ±1.5	40.0	100	380	2.93	40	0061500	•

• Upon availability.  
\* Tolerance on length: ± 1 % (ISO 1307 Standard)

#### Branding

