

PROJECTOR 40

PROJECTOR 40

BUILDINGS & CONSTRUCTION

Applications

For spraying of mortar and mixed concrete as well as dry products.
Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

Advantages

- Light weight, flexible and is easy to handle.
- Abrasion resistant tube compound.
- Conductive inner tube compound gives increased safety for the operator.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: wear and weather resistant SBR, black, fabric impression.

Temperature range: -30 °C to +70 °C.

Electrical properties: conductive tube, $R < 2 \cdot 10^6 \Omega/m$.

Special properties:

abrasion resistance of tube <70mm³ according to ISO 4649.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
25	7.0 ±0.50	39 ±1.0	10.0	40	125	0.86	20	0201452	1600
							40	0201453	1600
	9.5 ±0.50	44 ±1.0			120	1.29	20	0070670	200
							40	0070671	200
30	7.0 ±0.50	44 ±1.0	10.0	40	150	0.91	20	0201455	200
							40	0201456	200
32	10.0 ±0.50	52 ±1.0	10.0	40	150	1.65	20	0060192	200
							40	0060067	200
35	7.0 ±0.50	49 ±1.0	10.0	40	220	1.07	20	0070672	200
							40	0070673	200
38	10.0 ±0.50	58 ±1.0	10.0	40	170	1.88	40	5501052	200
40	10.0 ±0.50	60 ±1.0	10.0	40	180	1.97	20	0061716	•
							40	0061717	•
50	10.0 ±0.75	70 ±1.5	10.0	40	250	2.36	20	0061718	•
							40	0061719	•
60	10.0 ±0.75	80 ±1.5	10.0	40	290	2.64	20	0096832	•
							40	0096827	•
65	10.0 ±0.75	85 ±1.5	10.0	40	320	2.95	20	0061720	•
							40	0061721	•
70	10.0 ±0.75	90 ±1.5	10.0	40	350	3.2	20	0070674	160
							40	0070675	160
75	10.0 ±0.75	95 ±1.5	10.0	40	400	3.34	20	0070676	160
							40	0070677	160

• Upon availability.

* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding

