

# SABLEX

## SABLEX BUILDINGS & CONSTRUCTION

### Applications

For cleaning and shot blasting castings, metal, stone and concrete surfaces.

### Advantages

- Small tolerances, therefore easy to couple.
- Longitudinally stable i.e. the length will not alter under pressure (unstable hoses result in the operator losing control when pressure is applied).
- Light weight and flexible for easy handling.
- Conductive inner tube compound gives increased safety for the operator, since there is no risk of wire breakage in use.

### Technical description

**Inner tube:** wear resistant NR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** wear and weather resistant SBR, black, fabric impression.

**Temperature range:** -30 °C to +70 °C.

**Electrical properties:** conductive tube,  $R < 2 \cdot 10^6 \Omega/m$ .

### Special properties:

abrasion resistance of tube <70mm<sup>3</sup> according to ISO 4649.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
13	7.0 ±0.50	27 ±1.0	12.0	40	65	0.58	40	0060061	•
16	7.0 ±0.50	30 ±1.0	12.0	40	80	0.68	20	0028719	400
							40	0028720	400
19	7.5 ±0.50	34 ±1.0	12.0	40	100	0.78	20	0028745	•
							40	0028746	•
25	7.0 ±0.50	39 ±1.0	12.0	40	125	0.86	20	0060969	•
							40	0060970	•
32	8.0 ±0.50	48 ±1.0	12.0	40	160	1.3	20	0060971	•
							40	0060972	•
	11.0 ±0.50	54 ±1.0			140	1.85	20	0070785	200
							40	0070786	200
35	9.0 ±0.50	53 ±1.0	12.0	40	190	1.57	40	0070788	200
38	10.0 ±0.50	58 ±1.0	12.0	40	170	1.89	20	0070789	200
							40	0070790	•
40	10.0 ±0.50	60 ±1.0	12.0	40	180	1.97	20	0028786	600
							40	0028787	•
42	9.0 ±0.50	60 ±1.0	12.0	40	240	1.81	20	0070791	200
							40	0070792	200
50	10.0 ±0.75	70 ±1.5	12.0	40	250	2.36	40	0060974	•
63	10.0 ±0.75	83 ±1.5	12.0	40	325	2.9	40	0060077	160
65	10.0 ±0.75	85 ±1.5	12.0	40	320	2.95	20	0070797	160
							40	0070798	160
76	10.0 ±0.75	96 ±1.5	12.0	40	400	3.42	40	0070784	120
102	10.0 ±0.75	122 ±1.5	10.0	40	550	4.4	40	0028860	80

• Upon availability.

\* Tolerance on length: ± 1 % (ISO 1307 Standard)

### Branding

# SABLEX

Made in France



# TRELLEBORG