



SUPERVRAC AL

SUPERVRAC AL

MATERIAL HANDLING

Applications

Pneumatic transport of bulk abrasive products for the food industry. Discharge from road and rail tankers and delivery to storage bins: foodstuffs and chemicals (fertilizers, granulates, PVC, dye stuffs, etc.).

Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.

Technical description

Inner tube: foodgrade wear resistant NR, white, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, black, fabric impression.

Temperature range: -30 °C to +80 °C.

Electrical properties: non conductive tube with built-in wire.

Standard/Approval

FDA regulation 21 CFR 177.2600.



ID mm	Wall thickness mm		OD mm		Working pressure bar	Bursting pressure bar	Weight kg/m	Length m	Article number	Stock or min. order m
	mm	±	mm	±						
89	6.0	±1.00	101	±1.5	7.0	21	2.07	20	5503290	•
								40		
100	9.0	±1.25	118	±1.5	7.0	21	3.6	40	5513140	•
								40		
102	10.0	±1.25	122	±1.5	7.0	21	3.75	20	5503292	•
								40		
110	6.5	±1.25	123	±1.5	7.0	21	2.63	20	5503292	•
								40		

• Upon availability.
* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding

