

SUPERVRAC TAN

SUPERVRAC TAN

MATERIAL HANDLING

Applications

Pneumatic transport of bulk abrasive products. Discharge from road and rail tankers, and delivery to storage bins: cement, sand, lime and also cereals, fertilizers, cattle feed and chemicals (PVC, dye stuffs, granulates, etc.).

Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.

Technical description

Inner tube: heavy duty abrasion resistant NR, beige, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, black, fabric impression.

Temperature range: -30 °C to +70 °C.

Electrical properties: non conductive tube with built-in wire.



ID mm	Wall thickness mm		OD mm		Working pressure bar	Bursting pressure bar	Weight kg/m	Length m	Article number	Stock or min. order m
75	6.0	±1.25	87	±1.5	7.0	21	1.72	20	0070661	120
								40	0125111	120
85	6.0	±1.25	97	±1.5	7.0	21	1.81	20	0070662	80
								40	0070663	80
89	6.0	±1.25	101	±1.5	7.0	21	1.98	20	0060614	•
								40	0060615	•
100	6.0	±1.25	112	±1.2	7.0	21	2.24	20	0070664	120
								40	0070665	120
110	6.5	±1.25	123	±1.5	7.0	21	2.5	20	0060617	•
								40	0060618	•

• Upon availability.

* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding

