



# TRELLBLAST S

## TRELLBLAST S BUILDINGS & CONSTRUCTION

### Applications

For cleaning and shot blasting castings, metal, stone and concrete surfaces.

### Advantages

- Light weight and flexible for easy handling.
- Conductive inner tube compound gives increased safety for the operator, since there is no risk of wire breakage in use.

### Technical description

**Inner tube:** wear resistant NR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** wear and weather resistant SBR, black, fabric impression.

**Temperature range:** -30 °C to +70 °C.

**Electrical properties:** conductive tube,  $R < 2.10^6 \Omega/m$ .

### Special properties:

abrasion resistance of tube  $< 70mm^3$  according to ISO 4649.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
13	7.0 ±0.5	27 ±1	10.0	30	65	0.56	40	5026067	•
16	7.0 ±0.5	30 ±1	10.0	30	80	0.68	40	5026068	400
19	7.5 ±0.5	34 ±1	10.0	30	100	0.74	40	5501321	•
25	7.0 ±0.5	39 ±1	10.0	30	125	0.86	40	5501322	•
32	8.0 ±0.5	48 ±1	10.0	30	160	1.3	40	5501323	•

• Upon availability.

\* Tolerance on length: ± 1 % (ISO 1307 Standard)

### Branding

