



# TRELLVAC Excavator

## TRELLVAC Excavator CONSTRUCTION & MINING EQUIPMENT

### Applications

Working hose specially designed for suction excavators.

### Advantages

- Long lifespan thanks to the high quality NR tube and its large thickness.
- Easy replacement of the hose thanks to 254mm diameter.

### Technical description

- Inner tube:** wear resistant NR, black, smooth.
- Reinforcement:** synthetic textile with embedded steel helix.
- Cover:** SBR/NR, black, corrugated.
- Temperature range:** -30 °C to +80 °C.
- Electrical properties:** conductive tube and cover for 70ShA tube.

### Couplings/Fittings

Cuffed ends, length 70mm.

### Complementary information

- 40ShA tube: excellent hose flexibility.
- 70ShA tube: excellent abrasion and tear resistance (transport of sharp-edged stones).

Hoses are delivered in straight length, on pallet.



ID mm	OD mm	Max. vacuum bar	Bending radius mm	Weight kg/lg	Length m	Type	Article number	Stock or min. order m	
254 ±1.5	302	0.9	500	173	6,9	70ShA	5513548	•	
				200	7,9		5513549	•	
	307				140	5,3	40ShA	5513546	•
					181	6,9		5513547	•

☐ Upon availability.  
\* Tolerance on length: ± 1 % (ISO 1307 Standard)

### Branding

Yellow stripe for type 40ShA.



and embossed: week/year

