

TRELLVAC Extractor LD

TRELLVAC Extractor LD

CONSTRUCTION & MINING EQUIPMENT

Applications

Universal ducting hose for dust, wood chips, small particles and various types of gas.

Advantages

- Light and flexible.
- Excellent bending radius.
- Especially useful when low weight and easy handling are valued.

Technical description

Inner tube: wear resistant SBR/NR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: wear and weather resistant SBR/NR, black, corrugated.

Temperature range: -40 °C to +90 °C.

Electrical properties: conductive tube and cover, $R < 10^6 \Omega/m$.

Complementary information


OD measured on top of corrugation.



Resistance



Flexibility



Weight



ID mm	OD mm	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
38	44,5 ±1.0	0.9	45	0.62	12	0025890	•
51	57,5 ±1.0	0.9	70	0.81	12	0025908	•
63	70 ±1.0	0.9	95	0.87	12	0025916	•
76	83,5 ±1.0	0.9	115	1.04	12	0025932	•
90	97,5 ±1.0	0.9	125	1.22	12	0025965	•
102	110,5 ±1.0	0.9	145	1.57	12	0025973	•
113	121,5 ±1.5	0.9	155	1.73	12	0025981	•
127	135,5 ±1.5	0.7	170	1.93	12	0026005	•
152	160,5 ±1.5	0.4	195	2.3	12	0026013	•
178	186,5 ±1.5	0.25	220	2.68	12	0026021	12
204	212,5 ±1.5	0.15	245	3.06	12	0026039	•

• Upon availability.

* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding

