



TRELLVAC Handler HD

TRELLVAC Handler HD CONSTRUCTION & MINING EQUIPMENT

Applications

Heavy duty working hose on vacuum cleaning trucks for use at the work site.

Advantages

- Light and flexible with good wear resistance.
- TRELLVAC Handler HD is a working hose for heavy materials when wear resistance is of highest priority.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile, woven fabric with embedded steel helix..

Cover: wear and weather resistant SBR/NR, black, corrugated.

Temperature range: -30 °C to +90 °C.

Electrical properties: non conductive. The helix can be connected to couplings in both ends, Built-in conductive wire.


Complementary information

OD measured on top of corrugation.


ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
102	118 ±1.6	5.0	15	0.9	400	3.1	20	5513135	160
							40	2227830	160
127	143 ±1.6	5.0	15	0.9	500	3.8	20	5513136	120
							40	1580400	120
152	168 ±2.0	5.0	15	0.9	600	4.55	20	5513137	200
204	225 ±2.0	1.5	4.5	0.9	800	8.2	12	1869200	36



Resistance



Flexibility



Weight



±Upon availability.

* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding

TRELLVAC Handler HD

Made in France



TRELLEBORG