



TRELLVAC Handler LD

TRELLVAC Handler LD CONSTRUCTION & MINING EQUIPMENT

Applications

For industrial vacuum cleaners and cleaning systems.
Useful for suction of drainage sludge, sand, etc.

Advantages

- Light and flexible design.
- Very good wear resistance.
- Especially useful when low weight and easy handling are valued.

Technical description

Inner tube: wear resistant NR, black, smooth.
Reinforcement: synthetic textile cords with embedded steel helix.
Cover: wear and weather resistant SBR, black, corrugated.
Temperature range: -30 °C to +80 °C.
Electrical properties: non conductive. The helix can be connected to couplings in both ends

Complementary information

OD measured on top of corrugation.

ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
51	61 ±1.5	5.0	15	0.9	85	1.0	20	5500748	320
							40	2914510	•
60	70 ±1.5	5.0	15	0.9	105	1.15	20	5500749	120
							40	2914520	120
63	73 ±1.5	5.0	15	0.9	110	1.22	20	5500750	120
							40	2891580	•
76	86,5 ±1.5	5.0	15	0.9	135	1.5	20	5500751	120
							40	2913940	•



Resistance **Flexibility** **Weight**

☐ Upon availability.

* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding

