



# KLENET

## KLENET PROCESSING EQUIPMENT

### Applications

Washdown and cleaning in food processing industries, canneries, dairies, slaughterhouses, etc.

### Advantages

- Very good resistance to high temperatures.
- Smooth for easy handling with light-coloured, non-marking cover.
- Excellent resistance of the cover compound to animal and vegetable grease.
- Contains no phthalate.

### Technical description

**Inner tube:** food grade quality oil resistant NBR, white, smooth.

**Reinforcement:** synthetic textile.

**Cover:** oil and weather resistant NBR/PVC, blue, smooth.

**Temperature range:** -20 °C to +95 °C.

### Standard/Approval

For food product:

- EU regulations No. 1935/2004, 2023/2006.
- FDA regulation No. 21 CFR 177.2600.
- German legislation: BfR recommendation XXI cat. 3.
- French legislation.

All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

### Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

### Complementary information

Not recommended with washdown guns.

ID mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
13 ±0.5	21,4 ±0.7	10.0	30	80	0.3	20	0060962	•
						40	0060961	•
						60	0060952	4620
16 ±0.7	25 ±0.8	10.0	30	95	0.38	120	0060953	•
						20	0060964	•
						40	0060963	•
19 ±0.7	28,4 ±0.8	10.0	30	115	0.48	60	0060954	1440
						120	0060955	•
						20	0060966	•
25 ±1.0	35 ±1.1	10.0	30	155	0.62	40	0060965	•
						60	0060956	•
						20	0060968	•
						40	0060967	•
						60	0060957	1020

• Upon availability.  
\* Tolerance on length: ± 1 % (ISO 1307 Standard)

### Branding



and embossed: week/year - batch number