

MILLESIME

MILLESIME PROCESSING EQUIPMENT

Applications

Particularly designed for additional air lines (temperature up to 140°C) on road tankers carrying bulk products.

Suction and discharge of liquid food-stuffs such as milk, wine, beer, cider, fruit juice, soda, vinegar and alcohol up to 96% with exception of fatty foodstuffs and oils.

Loading or unloading bays for road and rails tankers.

Advantages

- Good flexibility and easy to handle.
- Suitable for road tankers equipment except compressor lines.
- A smooth, seamless, white food grade tube that does not propagate bacterial growth.
- Resistant to cleaning with most common detergents or with steam at max. +140°C.
- Cover with very good ageing and weather resistance.
- Contains no phthalate.

Technical description

Inner tube: food grade quality EPDM, white, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather resistant EPDM, blue, fabric impression.

Temperature range: -30 °C to +100 °C.

+140°C for additional air

Standard/Approval

For food product:

- EU regulations No. 1935/2004, 2023/2006.
- FDA regulation No. 21 CFR 177.2600.
- French legislation.

All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.



ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
25 -0/+1.0	36 ±1.0	10.0	30	0.9	55	0.81	20	5500495	•
							40	5500496	•
32 -0/+1.0	43 ±1.0	10.0	30	0.9	70	0.98	20	5500497	200
							40	5500498	200
38 -0/+1.0	49 ±1.0	10.0	30	0.9	80	1.15	20	5500499	•
							40	5500500	•
40 -0/+1.0	51 ±1.0	10.0	30	0.9	85	1.2	20	5500501	200
							40	5500502	200
45 -0/+1.0	56 ±1.0	10.0	30	0.9	98	1.32	20	5500505	160
							40	5500506	160
51 -0/+1.0	62,5 ±1.5	10.0	30	0.9	105	1.66	20	5500507	•
							40	5500508	•
53 -0/+1.0	64,5 ±1.5	10.0	30	0.9	110	1.72	20	5500509	120
							40	5500510	120
60 -0/+1.0	71,5 ±1.5	10.0	30	0.9	125	1.85	20	5501050	120
							40	5501051	120
63 -0/+1.0	74,5 ±1.5	10.0	30	0.9	130	2.0	20	5500511	•
							40	5500512	•
70 -0/+1.0	81,5 ±1.5	10.0	30	0.9	145	2.24	20	5500513	80
							40	5500514	80
76 -0/+1.0	88,5 ±1.5	10.0	30	0.9	165	2.95	20	5500515	•
							40	5500516	•

89	-0/+1.0	102	±1.5	10.0	30	0.9	330	3.44	20	5500517	□
									40	5500518	•
102	-0/+1.5	115	±1.5	10.0	30	0.9	400	3.8	20	5500521	□
									40	5500522	•
125	-0/+1.5	145,5	±2.0	10.0	30	0.9	480	7.2	10	5501067	•
									20	5501068	•
150	-0/+1.5	171,5	±2.0	10.0	30	0.9	570	8.8	10	5501069	80
									20	5501070	80

□ Upon availability.
 * Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding



and embossed: TRELLEBORG - MILLESIME - FDA - ND - WP 10bar - week/year - batch number - Made in France