





















## Percussion milling cutters

IMC recycling impact drilling cutters



	<b>14.200R</b>	<b>14.225R</b>	<b>14.250R</b>
	1 1/4	1 / 1 1/4	1 / 1 1/4
	8	9	10
	48	53	53
	3 × M10	3 × M10	3 × M10
	3 × M10	3 × M10	3 × M10
	—	—	—
	7 × 23	8 × 23	9 × 23
	95.6	101.4	115.7
	2,175	2,175	2,175
	✓	✓	✓



	Connecting thread [inch]		Rotating nozzles		Measures [inch]
	Application range [inch]		Thrust jet		Weight [lb.]
	min. gpm at 1450 psi at the nozzle		Front jet		Recycling

## Percussion milling cutters

### Accessory and wearing parts



#### Cutter head

14.200K → 14.200, changeable ∅ 8"

14.225K\* → 14.225, changeable ∅ 9"

14.250K → 14.250, changeable ∅ 10"

\* 14.225K in combination with 14.200 will need to order skid item no. 0014.2257

#### Hub

14.200NAR → 14.200K, 14.225K, 14.250K ∅ 8" - 10"



#### Diamond crown

0014.200D → 14.200K ∅ 8"

0014.250D → 14.250K ∅ 10"



#### Pull rod

14.1615ZS → pulling of the cutter ∅ 8" - 10"



#### Center head with hole

15.ZKB → cutters



#### Center head without hole

15.ZKW → cutters




#### Universal cutting tooth, can be used as offset application both inside and outside

15.ZU → cutters ∅ 8" - 10"



#### Universal cutting tooth, specifically for plastic pipes, can be used as offset application both inside and outside

15.ZU-GSL → cutters ∅ 8" - 10"



	Connecting thread [inch]		Rotating nozzles		Measures [inch]
	Application range [inch]		Thrust jet		Weight [lb.]
	min. gpm at 1450 psi at the nozzle		Front jet		Recycling




## Percussion milling cutters



### Universal cutting tooth for centre cap

15.Z1-ZK → cutters ∅ 8" - 10"



### Carbide tooth

15.ZHU → cutters ∅ 8" - 10"



### Diamond tooth

15.ZDSU-30 → cutters ∅ 8" - 10"



### Diamond tooth

15.ZDSU-60 → cutters ∅ 8" - 10"



### Swivel joint with thrust jets

24.125S → cutters ∅ 8" - 10"



### Cam plate

14.KR25W 0.09" Hub ∅ until 6"



	Connecting thread [inch]		Rotating nozzles		Measures [inch]
	Application range [inch]		Thrust jet		Weight [lb.]
	min. gpm at 1450 psi at the nozzle		Front jet		Recycling