

PERFORMER AD10H

PERFORMER AD10H

CONSTRUCTION & MINING EQUIPMENT

Applications

Hydraulic suction or discharge of abrasive materials.

Advantages

- Excellent resistance to abrasion.
- Low installation costs.
- Suppression of pressure surges.
- Reduction in pressure head loss.
- Damping of vibrations and noise.
- Many types of fittings possible.
- Excellent weather resistance.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather resistant EPDM, black, corrugated, fabric impression.

Temperature range: -30 °C to +70 °C.

Electrical properties: conductive tube and cover.

Couplings/Fittings

Hoses can be fitted with:

- 2 cuffed ends,
- 1 cuff + 1 END-FLEX® flange,
- 2 enlarged or smooth cuffs.

Hoses are fitted with END-FLEX® flanges (fitted hoses are allowed to work with pressure and vacuum mentioned in the table).

Complementary information

Low stretch under 10bar working pressure.

Hoses can be manufactured with straight or enlarged ends.



ID mm	OD mm	Tube thickness mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Min. length m	Max. length m	Length m	Article number	Stock or min. order m	
25	53	±2	5.6	10.0	30	0.9	125	2.13	0.5	20	0	HOCOHO37025	□
32	60	±2	5.6	10.0	30	0.9	160	2.56	0.5	20	0	HOCOHO37032	□
40	73	±2	8.5	10.0	30	0.9	200	3.53	0.5	20	0	HOCOHO37040	□
50	83	±2	8.5	10.0	30	0.9	250	4.2	0.5	20	0	HOCOHO37050	□
65	98	±2	8.5	10.0	30	0.9	325	5.05	0.5	20	0	HOCOHO37065	□
75	108	±2	8.5	10.0	30	0.9	375	5.65	0.5	20	0	HOCOHO37075	□
80	113	±2	8.5	10.0	30	0.9	400	5.94	0.5	20	0	HOCOHO37080	□
100	133	±2	8.5	10.0	30	0.9	500	7.33	0.5	20	0	HOCOHO37100	□
125	158	±2	8.5	10.0	30	0.9	750	8.64	0.5	20	0	HOCOHO37125	□
150	183	±2	8.5	10.0	30	0.9	1050	10.38	0.5	20	0	HOCOHO37150	□
175	208	±2	8.5	10.0	30	0.9	1300	11.93	0.5	10	0	HOCOHO37175	□
200	234,5	±2	8.5	10.0	30	0.9	1600	14.59	0.5	12	0	HOCOHO37200	□
250	285,5	±2	8.5	10.0	30	0.9	2000	17.5	1	12	0	HOCOHO37250	□
300	340,5	±2	8.5	10.0	30	0.9	2500	24.77	1	12	0	HOCOHO37300	□
350	391	±3	8.5	10.0	30	0.9	3000	30.62	1.5	12	0	HOCOHO37350	□
400	441	±3	8.5	10.0	30	0.9	4000	35.96	1.5	12	0	HOCOHO37400	□

500	548	±3	8.5	10.0	30	0.9	5000	53.35	2	12	0	HOCOHO3750 0	□
-----	-----	----	-----	------	----	-----	------	-------	---	----	---	-----------------	---

□ Upon availability.
* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding



and embossed: week/year