

SUPERVRAC

SUPERVRAC

MATERIAL HANDLING

Applications

Pneumatic transport of bulk abrasive products.
Discharge from road and rail tankers and delivery to storage bins (cement, sand, limestone, coal, etc.).

Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.
- Static conductive tube.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, black, fabric impression.

Temperature range: -30 °C to +90 °C.

Electrical properties: conductive tube and cover, $R < 10^6 \Omega/m$.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Weight kg/m	Length m	Article number	Stock or min. order m
75	6.75 ±1.25	88,5 ±2.0	7.0	21	1.83	20	0060675	120
						40	0060674	120
	9.0 ±1.00	93 ±1.5			2.75	20	0060189	▣
						40	0060193	•
85	6.0 ±1.00	97 ±1.5	7.0	21	2.03	20	0129699	120
						40	0129700	120
89	6.25 ±1.25	101,5 ±2.0	7.0	21	2.07	20	0060682	•
						40	0060683	•
100	6.0 ±1.00	112 ±1.5	7.0	21	2.4	20	0129701	120
						40	0129702	120
	9.0 ±1.00	118 ±1.5			3.58	20	0060194	•
						40	0060195	•
110	6.5 ±1.25	123 ±2.0	7.0	21	2.71	20	0060684	•
						40	5006696	200
127	8.5 ±1.25	144 ±2.0	7.0	21	4.2	20	0060685	120
						40	0060686	120
152	8.5 ±1.25	169 ±2.0	7.0	21	5.0	20	0060689	120
						40	0060690	120

▣ Upon availability.

* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding

