

BIOVAST RED

BIOVAST RED PROCESSING EQUIPMENT

Applications

For cleaning and wash-down operations in food industry.
Also suitable for transfer of aqueous, acidic, alcoholic or fatty liquid foodstuffs.

Advantages

- Can be used in any food industry environments (dairies, slaughterhouses, etc.).
- Highly flexible.
- Non staining cover.
- Contains no phthalate.

Technical description

Inner tube: food grade quality oil resistant NBR, white, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/PVC, red, smooth.

Temperature range: Water: -20°C to +100°C/WP=20bar.

Steam: +165°C/6bar

Standard/Approval

For food product:

- EU regulations No. 1935/2004, 2023/2006.
- FDA regulation No. 21 CFR 177.2600.
- French legislation.

All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

ID mm	OD mm	Working pressure (steam) bar	Bursting pressure bar	Working pressure (water) bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
13 ±0.8	23 ±0.9	6	60	20	65	0.36	20	5513767	•
							40	5513768	•
							60	5513769	•
16 ±1.0	26 ±1.0	6	60	20	85	0.43	20	5513770	•
							40	5513771	•
19 ±1.0	31 ±1.0	6	60	20	100	0.59	20	5513772	•
							40	5513773	•
25 ±1.0	37 ±1.0	6	60	20	125	0.69	20	5513774	•
							40	5513775	•

• Upon availability.

* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding



and embossed: week/year - batch number - 165°C - 6BAR